

JXP-B3210G-DL20D

XFP 10Gbps TX1330/RX1270nm SMF 20KM Simplex LC Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable XFP Footprint
- Supports upto 10Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 20KM on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with XFP MSA Specification
- Low power consumption

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JXP-B3210G-DL20D is a MSA compliant 10Gbps XFP Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

| | |
|---------------------|------------------|
| P/N | JXP-B3210G-DL20D |
| Form Factor | XFP |
| Standard & protocol | 10GBASE BX |
| Data Rate | 10Gbps |
| WaveLength | TX1330/RX1270nm |
| Media | SMF |
| Reach | 20KM |
| Interface | Simplex LC |
| Tx Source | DFB |
| Rx Source | PIN |
| Tx Power | -2~+3dBm |
| Rx Power | -15dBm |
| Temp. | Tc/Ti |