

JCP2-85112G-VM01D

CFP2 112Gbps 850nm MMF 100M MPO Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable CFP2 Footprint
- Supports upto 112Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 100M on MMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with CFP2 MSA Specification
- Low power consumption

Application

- Network Communication

- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JCP2-85112G-VM01D is a MSA compliant 112Gbps CFP/CFP2/CFP4 Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

P/N	JCP2-85112G-VM01D
Form Factor	CFP2
Standard & protocol	100GBASE SR4
Data Rate	112Gbps
WaveLength	850nm
Media	MMF
Reach	100M
Interface	MPO
Tx Source	VCSEL
Rx Source	PIN
Tx Power	-7.6 +2.4dBm
Rx Power	-8.7dBm
Temp.	Tc