

JP-Cxx12-DL80D

SFP 622Mbps CWDM 1470nm~1610nm SMF 80KM Duplex LC Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable SFP Footprint
- Supports upto 622Mbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 80KM on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with SFP MSA Specification
- Low power consumption

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JP-Cxx12-DL80D is a MSA compliant 622Mbps SFP Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

P/N	JP-Cxx12-DL80D
Form Factor	SFP
Standard & protocol	622M CWDM
Data Rate	622Mbps
WaveLength	CWDM 1470nm~1610nm
Media	SMF
Reach	80KM
Interface	Duplex LC
Tx Source	DFB
Rx Source	PIN
Tx Power	0~+5dBm
Rx Power	-28dBm
Temp.	Tc/Ti