

JDC-100GQP28-P2M

100Gb/s QSFP28 to QSFP28 2M 30 AWG Direct Attach Twinax Copper Cable



FEATURES & BENEFITS

- Hot-pluggable form-factor connectors
- Supports upto 100Gb/s Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link length Up to 2M on Copper Cable
- RoHS Compliant (lead free)
- Operating Case Temperature : 0~70
- Compliant with QSFP28 to QSFP28 MSA Specification
- Low power consumption

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JDC-100GQP28-P2M is a MSA compliant 100Gb/s QSFP28 to QSFP28 Packaged Passive Copper Cable. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

| | |
|-----------------|------------------|
| P/N | JDC-100GQP28-P2M |
| Data Rate | 100Gb/s |
| Media | Copper |
| Formfactor | QSFP28 to QSFP28 |
| Cable Type | Passive |
| AWG | 30 |
| Length | 2M |
| Operating Temp. | 0~70 |