

JP28-1325G-DL30D

SFP28 25Gbps 1310nm SMF 30km(without FEC) Duplex LC Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable SFP28 Footprint
- Supports upto 25Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 30km(without FEC) on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with SFP28 MSA Specification
- Low power consumption

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JP28-1325G-DL30D is a MSA compliant 25Gbps SFP28 Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

P/N	JP28-1325G-DL30D
Form Factor	SFP28
Standard & protocol	25GBASE ER Lite
Data Rate	25Gbps
WaveLength	1310nm
Media	SMF
Reach	30km(without FEC)
Interface	Duplex LC
Tx Source	DFB
Rx Source	APD
Tx Power	-3.0 +6.0dBm
Rx Power	-19.0dBm
Temp.	Tc/Ti