

JTFA206-P-P

6x 10/100Base-TX to 2x 100Base-FX SFP Port Unmanaged Fast Ethernet PoE Industrial Switch



FEATURES & BENEFITS

- Complies with IEEE 802.3 ,IEEE 802.3u ,IEEE 802.3x ,IEEE 802.3af/at PoE
- 6x 10/100Base-TX with IEEE 802.3af/at PoE
- 2x 100Base-FX
- Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
- Redundant Power Design
- Power Polarity Reverse Protection
- Overload Current Protection
- Max 160KM based on SFP spec
- Operating Case Temperature : -40~75
- DIN-Rail or Wall Mountable
- IP30 Corrosion resistant aluminum case

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JTFA206-P-P is an unmanaged Fast Ethernet is equipped with 6x 10/100Base-TX (IEEE 802.3af/at PoE) and 2x 100Base-FX interfaces that provides reliable and cost-effective network connectivity and fiber extension in harsh industrial environments, It is specifically designed supporting up to 30 Watts PoE per port to fulfill industrial applications such as industrial automation, security, power/utility, oil and gas, mining and outdoor environment.

SPECIFICATIONS

Data Rate	10/100Mbps
Device Type	Unmanaged

Interface Characteristics

Copper Interface	6x 10/100Base-TX (IEEE 802.3af/at PoE)
Fiber Interface	2x 100Base-FX
Wavelength	Based on SFP Spec
Media	Based on SFP Spec
Distance	Based on SFP Spec
Connector	SFP Port
LED indicators	PWR (power supply); FL/A (optical link/action) FDX (FX full duplex), TL/A (twisted pairs link/action) 100 (100M transmission rate of twisted pairs), FX (100M transmission rate of optical fiber)

Technology

Standards and Protocols	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Full duplex and flow control IEEE 802.3af/at PoE
Processing Type	Store and Forward
Flow Control	Half-duplex back-pressure and IEEE 802.3x full-duplex flow control

Power

Power Input	DC 12~52V
PoE Standard	IEEE 802.3af/at PoE
PoE Power Budget	30W Per PoE Port
Power Consumption	<4W
Protection	Overload current protection Reverse polarity protection

Switch Properties

Switching Capacity	1G
Forwarding Rate	0.1488Mbps
MAC address table	1K
Packet Buffer	448K
Jumbo Frame	1552/1536/bytes
Delay	<3μs

Physical

Casing Mat.	Aluminum, IP30
Dimensions	143 x 101 x 44mm
Installation	DIN-Rail
Environmental	Operating temperature : -40~75°C Storage Temperature: -40~85°C Relative Humidity: 5% to 95% non-condensing

Regulatory

ISO	Manufactured in ISO-9001 facility
Safety & Emission	CE , FCC, RoHS
EMI	FCC Part 15B Class A EN 61000-6-4 EN 61000-3-2 EN 61000-3-3
EMS	EN 61000-6-2 EN 61000-4-2 (ESD Standards) EN 61000-4-3 (Radiated RFI Standards) EN 61000-4-4 (Burst Standards) EN 61000-4-5 (Surge Standards) EN 61000-4-6 (Induced RFI Standards) EN 61000-4-8 (Magnetic Field Standards)
Stability	IEC 60068-2-6 Fc (Vibration) IEC 60068-2-27 Ea (Shock) IEC 60068-2-32 Ed (Free fall w/package)

Reliability

MTBF	>50,000Hrs
------	------------

Mechanical Dimensions

143 x 101 x 44mm(LxWxH)

