

JTGA102-B53S40-P

2x 10/100/1000Base-TX to 1x 1000Base-FX (Tx1550nm/Rx1310nm SMF 40km Single SC) Unmanaged Gigabit Ethernet PoE Industrial Switch



FEATURES & BENEFITS

- Complies with IEEE 802.3 ,IEEE 802.3u ,IEEE 802.3ab ,IEEE 802.3z 1000BASE-X Gigabit FiberIEEE 802.3x ,IEEE 802.3af/at PoE
- 2x 10/100/1000Base-TX with IEEE 802.3af/at PoE
- 1x 1000Base-FX
- Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
- Redundant Power Design
- Power Polarity Reverse Protection
- Overload Current Protection
- Extends fiber distance up to 40km
- Operating Case Temperature : -40~75
- DIN-Rail or Wall Mountable
- IP30 Corrosion resistant aluminum case

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JTGA102-B53S40-P is an unmanaged Gigabit Ethernet is equipped with 2x 10/100/1000Base-TX (IEEE 802.3af/at PoE) and 1x 1000Base-FX interfaces that provides reliable and cost-effective network connectivity and fiber extension in harsh industrial environments, It is specifically designed supporting up to 30 Watts PoE per port to fulfill industrial applications such as industrial automation, security, power/utility, oil and gas, mining and outdoor environment.

SPECIFICATIONS

Data Rate	10/100/1000Mbps
Device Type	Unmanaged

Interface Characteristics

Copper Interface	2x 10/100/1000Base-TX (IEEE 802.3af/at PoE)
Fiber Interface	1x 1000Base-FX
Wavelength	Tx1550nm/Rx1310nm
Media	SMF
Distance	40km
Connector	Single SC
LED indicators	PWR (power supply); FL/A (optical link/action) FDX (FX full duplex), TL/A (twisted pairs link/action) 100 (100M transmission rate of twisted pairs), FX (100M transmission rate of optical fiber)

Technology

--	--

	IEEE 802.3x Full duplex and flow control IEEE 802.3af/at PoE
Standards/Type/Protocols	IEEE 802.3 10BASE-T IEEE 802.3 100BASE-T
Flow Control	IEEE 802.3x backpressure and IEEE 802.3x full-duplex flow control
Power	IEEE 802.3ab 1000BASE-T
Power Input	IEEE 802.3z 1000BASE-X Gigabit Fiber DC 12~52V
PoE Standard	IEEE 802.3af/at PoE
PoE Power Budget	30W Per PoE Port
Power Consumption	<4W
Protection	Overload current protection Reverse polarity protection

Switch Properties

Switching Capacity	6G
Forwarding Rate	1.488Mbps
MAC address table	2K
Packet Buffer	2MB
Jumbo Frame	9K
Delay	<3 μ s

Physical

Casing Mat.	Aluminum, IP30
Dimensions	118 x 86 x 39mm
Installation	DIN-Rail
Environmental	Operating temperature : -10~55°C Storage Temperature: -40~85°C Relative Humidity: 5% to 95% non-condensing

Regulatory

ISO	Manufactured in ISO-9001 facility
Safety & Emission	CE , FCC, RoHS
EMI	FCC Part 15B Class A EN 61000-6-4 EN 61000-3-2 EN 61000-3-3

	EN 61000-4-6 (Induced RFI Standards) EN 61000-4-8 (Magnetic Field Standards)
EMC	IEC 60068-2-2 Fc (Vibration) IEC 60068-2-27 Ea (Shock) IEC 60068-2-32 Ed (Free fall) IEC 61000-4-2 (ESD Standards)
Reliability	EN 61000-4-3 (Radiated RFI Standards)
MTBF	EN 61000-4-4 (Burst Standards) >50,000Hrs EN 61000-4-5 (Surge Standards)

Mechanical Dimensions

118 x 86 x 39mm(LxWxH)

