

JDMX-XXXX-A06D

6 Channels DWDM OADM 1U Chassis / LGX Package Optional system
Ch21~60 Wavelength Optional



FEATURES & BENEFITS

- Compliant to DWDM ITUT G.694.1 H Band 100GHz
- Adding or dropping of up to 6 CWDM wavelengths
- Protocol transparent, support 1G, 10G, 100G etc
- Low insertion loss
- LC/UPC connectors
- Passive, no electric power is required
- High stability and reliability
- 19" 1U Rackmount system
- Custom design supported

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JDMX-XXXX-A06D is a 1U Chassis / LGX Package Optional packaged Dual Fiber DWDM OADM system. It is specifically designed to easily add or drop 6 Ch DWDM Ch21~60 traffic from a DWDM Stream. It is fully protocol transparent and to perfectly fulfill applications including 1G/10G/100G Ethernet, SDH/SONET, 1/2/4/8/16/32G Fibre Channel/FICON, CATV and FTTx.

SPECIFICATIONS

Access Type	Dual Fiber	
Channels	6	
EXP	/	
MON	/	
Packaging	1U Chassis / LGX Package Optional	
Dimension	44x483x250mm	mm
Center Wavelength	Ch21~60	nm
Channel Spacing	100	GHz
Channel Passband	±0.11	nm
Center Wavelength Accuracy	±0.05	nm
Channel Uniformity	< 1.0	dB
Adjacent channel isolation	> 30	dB
Non adjacent channel isolation	> 40	dB
Directivity	> 55	dB
Return Loss	> 50	dB
PDL	< 0.15	dB
PMD	< 0.1	ps
Wavelength thermal stability	< 0.003	nm/°C
Insertion Loss thermal stability	< 0.005	nm/°C
Power Handling	< 300	mW
Operating temperature	0 ~ +70	°C
Storage temperature	-40 ~ +85	°C