

# JQ28-CX100GX-DL2D

QSFP28 103.1~112Gbps CWDM 1271nm~1331nm SMF 2KM Duplex LC  
Optical Transceiver



## FEATURES & BENEFITS

- Hot-Pluggable QSFP28 Footprint
- Supports upto 103.1~112Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link length Up to 2KM on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with QSFP28 MSA Specification
- Low power consumption

## Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

## OVERVIEW

JQ28-CX100GX-DL2D is a MSA compliant 103.1~112Gbps QSFP28 Packaged Transceiver. It is designed,assembled,tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

## SPECIFICATIONS

P/N	JQ28-CX100GX-DL2D
Form Factor	QSFP28
Standard & protocol	100GBASE CWDM4
Data Rate	103.1~112Gbps
WaveLength	CWDM 1271nm~1331nm
Media	SMF
Reach	2KM
Interface	Duplex LC
Tx Source	CWDM DFB
Rx Source	PIN
Tx Power	-6.5~+2.5dBm
Rx Power	-11.5dBm
Temp.	Tc