

JPP-1310G-FL2D

SFP+ 10Gbps 1310nm SMF 2KM Duplex LC Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable SFP+ Footprint
- Supports upto 10Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 2KM on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with SFP+ MSA Specification
- Low power consumption

Application

- Network Communication

- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JPP-1310G-FL2D is a MSA compliant 10Gbps SFP+ Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

P/N	JPP-1310G-FL2D
Form Factor	SFP+
Standard & protocol	10GBASE IR
Data Rate	10Gbps
WaveLength	1310nm
Media	SMF
Reach	2KM
Interface	Duplex LC
Tx Source	FP
Rx Source	PIN
Tx Power	-8.2~+0.5dBm
Rx Power	-12.6dBm
Temp.	Tc/Ti