

JPP-Cxx10G-EL60DX

SFP+ 10Gbps CWDM 1270nm~1450nm SMF 60KM Duplex LC Optical Transceiver



FEATURES & BENEFITS

- Hot-Pluggable SFP+ Footprint
- Supports upto 10Gbps Data Rates
- Single 3.3V Power Supply and Industry Low Power dissipation
- Max link lenght Up to 60KM on SMF Fiber
- Class 1 Laser Safety Compliant
- RoHS 6 compliant (lead free)
- Operating Case Temperature : 0~70 (Extended /Industrial grade optional)
- Compliant with SFP+ MSA Specification
- Low power consumption

Application

- Network Communication
- FTTH/FTTB/FTTx
- ISP Backhaul Networking

OVERVIEW

JPP-Cxx10G-EL60DX is a MSA compliant 10Gbps SFP+ Packaged Transceiver. It is designed, assembled, tested in the ISO certified manufacturing facilities and an ideal choice to fulfill various optical Networking applications.

SPECIFICATIONS

P/N	JPP-Cxx10G-EL60DX
Form Factor	SFP+
Standard & protocol	10GBASE CWDM
Data Rate	10Gbps
WaveLength	CWDM 1270nm~1450nm
Media	SMF
Reach	60KM
Interface	Duplex LC
Tx Source	EML
Rx Source	APD
Tx Power	$\geq +1$ dBm
Rx Power	-20dBm
Temp.	Tc/Ti